


# Bandsaw Lubricant

**Product Code:** OCFNBLUBRICANT | **Revision:** 20220323



Mineral oil based general purpose lubricant.

## Available Pack Sizes



## Applications

Premium quality paraffinic base oils providing rust and oxidation resistance, ideal for applications such as bearings, machine tools, roller chains, drive chains and all general purpose lubrication applications.

Recommended by EPS Services & Tooling as suitable for the following applications

Suitable for the lubrication of enclosed circulating systems. These oils are also suitable for all general lubrication uses

## Benefits

- Demulsifying to ensure rapid water separation.
- Good corrosion protection.
- High thermal stability.
- Low ash formulation.
- Provides good oxidation resistance.

## Typical Test Data

Density @ 15°C (kg/m <sup>3</sup> )	ASTM D4052	0.82
Flash Point (°C)	ASTM D92	>90
Kinematic Viscosity @ 40°C (mm <sup>2</sup> /s)	ASTM D445	5
Pour Point (°C)	ASTM D97	--

The typical test data provided is taken from average values, there will be some variability in production and therefore do not constitute a specification.

## Health, Safety & Recommendations

- A Safety Data Sheet is available for consultation at [www.eps-services.co.uk](http://www.eps-services.co.uk).
- Packaging should not be left exposed to elements and drums should be laid horizontally to prevent contamination.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- When disposing of the product after use, please protect the environment and comply with local regulations.

Specialists in Saw Manufacturing Service and Repair

**EPS** SERVICES & TOOLING

Somerset Tel: +44 (0) 1984 624273

Fife Tel: +44 (0) 1592 654990

Essex Tel: +44 (0) 1245 890221

[www.eps-services.co.uk](http://www.eps-services.co.uk)