

GERRYMET SAW BLADES & TOOLING

PRODUCT DATA SHEET

BANDSAW NEAT BIO34 OIL

Product Code: OCFIBCOB34, OCF205OB34, OCF20OB34 & OCF5OB34



EPS Bandsaw Bio Oils are mineral oil free, high performance readily biodegradable lubricant for band saw and circular saw blades. Developed using specially selected additives and vegetable oil, these saw blade oils provide highly-effective lubrication with minimum impact on the environment and operators.

Applications

The Lubrisolve Bandsaw Bio Oils range has been formulated as an environmentally responsible saw blade oils and offer the following benefits:

Recommended by EPS Services & Tooling as suitable for the following applications

Suitable for the lubrication of enclosed circulating systems. These oils are also suitable for all general lubrication uses

Benefits

- · A readily biodegradable lubricant, free of genetically modified ingredients.
- · Excellent lubricity, leading to extended blade life.
- · Good oxidation stability.
- · Good corrosion protection.
- · Excellent operator acceptability.
- · Spray mist MQL application or flood applied.

Available Pack Sizes









Technical Data

| | KV @ 40°C | Specific Gravity @ 15°C | Odour | Appearance | Flash Point (°C) (COC) |
|--------------------|--------------|----------------------------|-------|-----------------|------------------------|
| Bandsaw Oil Bio 6 | 6 | 0.902 | Bland | Very Pale Straw | 160 |
| Bandsaw Oil Bio 15 | 15 | 0.912 | Bland | Very Pale Straw | 220 |
| Bandsaw Oil Bio 34 | 34 | 0.918 | Bland | Very Pale Straw | 230 |

Health, Safety & Recommendations

- $\cdot \, \text{A Safety Data Sheet is available for consultation at www.eps-services.co.uk}.$
- · Packaging should not be left exposed to elements.
- This product should not be stored at temperatures over 60°C, kept out of direct sunlight, protected from frost and fluctuations in temperature.
- · When disposing of the product after use, please protect the environment and comply with local regulations.

The content of this data sheet is given in good faith and without warranty.

No warranty of merchantability, fitness for any use, or any other warranty is expressed or to be implied, regarding the accuracy of this data. The results to be obtained from the use thereof, or the hazards connected with the use of this product. Lubrisolve Engineering Solutions Ltd. assumes no liability for any alleged ineffectiveness of the product or any injury or damage, direct

or consequential, resulting from the use of this product unless such injury or damage is solely attributable to negligence on the part of Lubrisolve Engineering Solutions Ltd.

Head Office: EPS Services & Tooling Ltd

Unit 2 Edwards Industrial Estate

Wiveliscombe, Taunton

Somerset TA4 2TU

Telephone number: 01984 624273

Issue: 08.06.23 Revision No.: 1.00 Date last revision: 08.06.2023

VAT Registration: GB 106003184 Company Registration: 07458736